

Specifications

GENERAL

| | |
|----------------------------|---|
| Type: | Console |
| Copy system: | Dry, electrostatic transfer system |
| Paper size: | Max. 11" x 17" / Min. 5.5" x 8.5" |
| Paper capacity: | 2,000 sheets |
| Copy/print speed (max): | 35/45 cpm/ppm (8.5" x 11") |
| Memory: | 320MB RAM and internal 5GB HDD standard |
| Warm-up time: ¹ | Less than 80 seconds |
| First copy time: | 5.3 sec. (35ppm); 4.6 sec. (45ppm) (8.5" x 11", 1st paper tray, fast platen mode) |
| Power requirements: | Rated local AC voltage \pm 10%, 50/60 Hz |
| Power consumption: | Max. 1.44 kW |
| Dimensions (WxDxH): | 32 7/16" x 26 11/64" x 43 37/64" (incl. scanner and paper desk) |
| Weight: | Approx. 220 lbs. (incl. scanner and paper desk) |
| Account codes: | 100 |

PRINTING (Standard)

| | |
|------------------|--|
| Resolution: | 600 dpi, 1,200 dpi enhanced with smoothing technology |
| Interface: | RJ-45 Ethernet with IP/MAC/Protocol filtering; IEEE1284 Parallel Port |
| Printer drivers: | Windows® 95/98/Me, Windows NT® 4.0, Windows® 2000, Windows® XP, Macintosh System 8.5.1-10.2 |
| PDL: | PCL5e, PCL6, Emulated PostScript Level 3 standard |
| Available fonts: | 45 fonts for HP PCL, 136 fonts for PS |
| Other features: | Paper/output tray selection, duplex print, watermarks, pamphlet style, job retention for confidential/sample print, N-up, B&W reverse, mirror image, form overlay, fit to page, auto configuration, easy print (stores settings), confidential print, sample print. Note: some features are not available on all print drivers. |

NETWORK SCANNING (Standard on all "S" and "F" models, optional on "N" models)

| | |
|----------------------|---|
| Resolution: | 200, 300, 600 dpi |
| Compatibility: | TWAIN compliant (push out method) |
| Sharpdesk licenses: | 10-user licenses included (can add 1,5,50 & 100 packs) |
| Max. original size: | 11"x17", duplex document - can scan up to 31" in length |
| Destinations: | Scan to E-mail, Scan to Fax, Scan to I-Fax, Scan to Desktop, Scan to FTP, Scan to Group |
| File types: | Single or Multi-page TIFF and PDF |
| User authentication: | Supports Anonymous, Simple, NTLM, Digest-MD5, Kerberos |

NETWORK INTERFACE (Standard on all DM models)

| | |
|----------------------|---|
| Type: | RJ-45 ethernet, 10Base-T/100Base-TX |
| Platforms supported: | UNIX, Windows 95/98/Me, Windows NT 4.0, Windows 2000, Windows XP, Novell Netware 3.x/4.x (IntranetWare)/Netware5, Macintosh System 8.5.1-10.2 |
| Network protocols: | IPX/SPX, TCP/IP, EtherTalk, NetBEUI |
| Printing protocols: | Novell Printserver Application w/NDS and Bindery, Printer resident LPD, IPP |

COPYING (standard)

| | |
|------------------|---|
| Original size: | Max. 11" x 17" - can scan up to 31" in length |
| Continuous copy: | Max. 999 copies |
| Resolution copy: | 600 dpi |
| Zoom range: | From 25% to 400% with 8 preset ratios (4 reduction + 4 enlargement), from 25% to 200% from DSPF |
| Other features: | Auto paper selection, auto magnification selection, paper type selection, auto tray switching, E-Sort, rotation copy, reserved copy, pre-heat/auto power shut-off modes, copy auditing (100 accounts), margin shift, edge/centre erase, dual page copy mode, multi-shot copy (N in 1), booklet copy |

Faxing (standard on "F" models, optional on "N" and "S" models)

| | |
|---------------------------------|---|
| Transmission time: ² | Approx. 2 seconds (Super G3): 6 seconds (G3) |
| Compression method: | MH, MR, MMR, JBIG |
| Modem speed: | 33.6Kbps/2.4Kbps automatic fallback |
| Transmission mode: | Super G3, G3 |
| Line type: | PSTN, PBX |
| Image quality: | 256 grayscale levels |
| Exposure adjustment: | Dark/Auto/Light |
| Resolution settings: | Normal/Small Letter/Fine/Extra Fine |
| Auto dial destinations: | 500 (e-mail addresses included) |
| PC fax: | Direct fax from Windows applications (standard) |

OPTIONS

Choose from 3 finishing options (saddle-stitch finisher, 2-bin stapler finisher or mailbox sorter). Please contact your DM-Series Reseller for further details.

LIMITED WARRANTY

All DM models come with Sharp's 1 Year, On-Site, Next-Day, parts and labor, limited warranty. 1 and 2 Year Next-Day or Same-Day warranty extensions and Installation Packages are also available. Contact your Sharp DM-Series Reseller for more information.

Design and specifications are subject to change without notice.

Sharp is a registered trademark of Sharp Corporation. All other trademarks are property of their respective holders.

¹ At rated voltage, 20 C (68 F), 65% RH.

² Based on ITU-T Test Chart #1 in standard resolution. Actual transmission time will vary based on line conditions.



As an ENERGY STAR® Partner, SHARP has determined that this product meets the ENERGY STAR® guidelines for energy efficiency.

Sharp Electronics Corporation
Sharp Plaza, Mahwah, NJ 07430-1163
1-800-BE-SHARP
www.sharppusa.com

SHARP®